

CAT# MTS-79

NO. POLES	MODEL NO.	SWITCH FUNCTION			CONNECTED TERMINALS			SCHEMATIC
		POS. 1	POS. 2	POS. 3	POS. 1	POS. 2	POS. 3	
		KEYWAY	KEYWAY	KEYWAY	KEYWAY	KEYWAY	KEYWAY	
DPDT	7215	MOM.	ON	MOM.	2-3,5-6	2-3,5-4	2-1,5-4	

1/4-40 UNS-2A
25°
POS 3
KEYWAY
POS 2
POS 1
.115 DIA. (2,920)
.420 (10,67)
.350 (8,89)
.155 (3,94)
.060 (1,52)
.030 TYP. (0,76)
.185 TYP (4,70)
EPOXY SEAL
.350 (8,89)

.190 (4,83)
.040 (1,02)
.500 (12,70)
.080 TYP. (2,03)
TERM. WIDTH
.450 (11,43)
Terminal Numbers For Reference Only

WIRING FOR 3-WAY SWITCHES

3-Position toggle and rocker switches with ON-ON-ON switch functions may be externally wired for '3-way' function. See wiring diagram and schematics below. **Note:** Jumpers are added by customer.

<p>Keyway C&K marking opposite side. POS. 3 POS. 2 POS. 1</p>	<p>To make single pole, 3-position switch using X211, X213, X215 model switches.</p>
	<p>(OUT) 6 3 2 (IN) 4 5 1</p>
	<p>6 3 2 (IN) (OUT) 4 5 1</p>
	<p>6 3 2 (IN) 4 5 1 (OUT)</p>