



ELECTRICAL CHARACTERISTICS: (671-8381 COMPATIBLE)

- 1 D.C.R. : PIN 1-3 = 150 OHM +/- 10%
PIN 4-6 = 140 OHM +/- 10%
- 2 INDUCTANCE : (@ 300KHZ, 1Vrms, W/H 80mADC) PIN 1-3 = 350mH MIN.
- 3 IMPEDANCE = 600 OHM +/- 5% (@ 400KHZ, 1Vrms, W/H 80mADC, 4-6 W/H 365 OHM)
- 4 INSERTION LOSS = 3.0dB MAX. (@ 1KHZ, 1Vrms, W/H 80mADC, 4-6 W/H 385 OHM)
- 5 FREQ. RESP. (REF. 1KHZ) @ 300KHZ = +/- 1.5dB @ 4KHZ = +/- 0.1dB
- 6 RETURN LOSS : (REF. 600 OHM) @ 400KHZ = 11dB MIN.
@ 1KHZ = 16dB MIN.
@ 4KHZ = 16dB MIN.
- 7 LOGITUDINAL BALANCE = 70dB MIN. (AT 1KHZ)
- 8 THD : (@ 600KHZ - 10dBm, W/H 80mADC) = -83dB MAX.
- 9 HI-POF = 1250mV, 1mV, 2SEC. (PRI-SEC)

REVISEMENTS		DATE		BY		CHK		APP	
A	12.95 MAX.								
NO	REVISION	DATE	BY	CHK	APP	Altech Altech Technology Co. USA 06/28/96 DATE M/M TRANSFORMER ATS-166 SHEET 1 OF 1 DRAWING Part			